

ETHERNET ACTIVATOR

BUILD ONTO
YOUR NETWORK

Ethernet Activator



beadedstream
beadedstream.com



SCAN FOR MORE

Add **beadedstream** Digital Temperature Cables (DTCs) on to your LAN with the Ethernet Activator. Take advantage of structured cabling that already exists in your building. Save time. Save money. Use existing Cat 5/6, switches, routers, the Internet, and in-house MIS expertise to build out your temperature monitoring network.

ETHERNET ACTIVATOR



SPECIFICATIONS

Access Remotely	<ul style="list-style-type: none">• Receive real-time data and remotely configure
Programmatic Interfaces	<ul style="list-style-type: none">• HTTP, HTTP POST, SNMP, TCP Socket, Multicast, DHCP
Responsiveness	<ul style="list-style-type: none">• Does not require temperature conversion• Real-time graphing and logging
Capacity	<ul style="list-style-type: none">• 500 ft (152.5 m) - maximum DTC length
Connections	<ul style="list-style-type: none">• RJ12 jack (DTC). Supports 1 DTC up to 125 sensors.• Ethernet RJ45 jack (data)• Micro USB (power/configuration)
Power and Protection	<ul style="list-style-type: none">• 5V USB charger to standard duplex outlet (USA) included.• Over 27kV static discharge protection on data line
Weight and Dimensions	<ul style="list-style-type: none">• 0.3 lbs (0.15 kg)• 4.5 in x 2.5 in x 1.25 in (11.5 cm x 9 cm x 3 cm)
Mounting	<ul style="list-style-type: none">• DIN Rail